

CENTARA



**CENTARA 2025
PRODUCT CATALOG**

Passenger and Light Truck Tires

CENTARA



GRAND TOURER H/T

- Four wide longitudinal water-escaping grooves and spacious transverse water-escaping grooves enhance water dispersion, providing excellent traction and braking on wet roads.
- Powerful with the luxurious SUV-oriented UHP tire.
- Outstanding performance on all roads with the wide tread and high groove-sipe ratio. Tranquil ride with the ideal pitch design and the variable sound frequency blocks. Special quality with good performon anti-puncture, underlay-damage and anti-friction from the unique sidewall protection layer.

GRAND TOURER H/T

SIZE	LOAD INDEX	SPEED RANGE	PLY
205/70R15	96	H	-
255/70R15	108	H	-
235/60R16	100	V	-
215/65R16	98	H	-
225/70R16	103	H	-
235/70R16	106	H	-
245/70R16	107	H	-
255/70R16	111	H	-
265/70R16	112	H	-
275/70R16	114	H	-
235/55R17	99	V	-
275/55R17	109	H	-
215/60R17	96	H	-
225/60R17	99	V	-
235/60R17	102	V	-
215/65R17	99	V	-
225/65R17	102	V	-
235/65R17	108	VXL	-
245/65R17	107	H	-
265/65R17	112	H	-
275/65R17	115	H	-
285/65R17	116	H	-
265/70R17	115	H	-
215/55R18	95	V	-
225/55R18	98	V	-
235/55R18	100	V	-
255/55ZRF18	109	VXL	-
225/60R18	100	H	-
235/60R18	107	VXL	-
235/65R18	106	H	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
255/60R18	108	H	-
265/60R18	110	H	-
245/60R18	105	V	-
265/65R18	114	H	-
255/70R18	113	H	-
265/70R18	116	T	-
235/45R19	95	V	-
255/45R19	100	V	-
235/50R19	99	V	-
245/50ZR19	105	WXL	-
255/50ZR19	107	WXL	-
265/50ZR19	110	WXL	-
225/55R19	99	V	-
235/55R19	105	VXL	-
245/55ZR19	103	W	-
255/55R19	111	VXL	-
275/55R19	111	W	-
265/45ZR20	104	W	-
265/50R20	111	VXL	-
275/50ZR20	113	WXL	-
285/50R20	112	V	-
235/55R20	105	VXL	-
275/60R20	115	H	-
265/45R21	108	VXL	-
275/45ZR21	110	WXL	-
275/50R21	113	VXL	-
275/50R22	111	V	-
255/55ZRF18	105	W	-
255/50ZRF19	103	W	-



ADVENTURE A/T



- Rectangle shoulder and wide tread design with 3D multiple thin sipes increases road contact area, provides superior handling on both wet and dry surfaces, and enhances wear-resisting performance.
- Wide pyramidal-shaped sipes for all-weather and various roads delivers excellent safety, maintains firm grip performance and aquaplaning resistance on wet roads, and enhances off-road steering response.
- Optimized pitching sequence blocks design offers quieter ride.
- Unique lateral flange protector design enhances protection from puncture and impact damage.

ADVENTURE A/T

SIZE	LOAD INDEX	SPEED RANGE	PLY
LT215/75R15	100/97	S	6PR
LT235/75R15	116/113	S	10PR
31X10.50R15LT	109	S	6PR
235/70R16	106	T	-
LT245/70R16	118/115	S	10PR
LT255/70R16	115/112	S	8PR
LT265/70R16	121/118	S	10PR
LT245/75R16	120/116	S	10PR
LT265/75R16	123/120	S	10PR
LT285/75R16	122/119	S	8PR
225/65R17	106	H	-
LT235/65R17	109/105	Q	8PR
LT245/65R17	111/108	S	8PR
LT265/65R17	120/117	S	10PR
LT245/70R17	119/116	S	10PR
LT285/70R17	121/118	S	8PR
235/60R18	107	HXL	-
LT265/60R18	119/116	S	10PR
285/60R18	120	HXL	-
LT265/65R18	122/119	S	10PR
LT285/65R18	125/122	S	10PR
LT285/50R20	119/116	Q	10PR



e.VANTI EV7



- Asymmetric pattern design provides better maneuverability.
- Multi-pitch and narrow groove width render better mute effect.
- Narrow groove on the outer side increases mileage and improves handling performance.
- Inner irregular broken-line design lowers down noise.

e.VANTI EV7

SIZE	LOAD INDEX	SPEED RANGE	PLY
205/50ZR17	93	WXL	-
215/50R17	95	VXL	-
205/55R17	95	VXL	-
215/55R17	98	VXL	-
235/45ZR18	98	WXL	-
255/45ZR18	103	WXL	-
245/45ZR19	102	WXL	-
255/45ZR19	104	WXL	-
235/50R19	103	VXL	-
235/40ZR19	96	WXL	-
255/40ZR19	100	WXL	-
255/45ZR20	105	WXL	-
235/50ZR20	104	WXL	-
245/50ZR20	105	WXL	-
255/50R20	109	VXL	-
255/55ZR20	110	WXL	-
255/45ZR21	106	WXL	-



VANTI HP

SIZE	LOAD INDEX	SPEED RANGE	PLY
195/45R16	84	VXL	-
205/45R16	87	WXL	-
175/50R16	77	V	-
185/50R16	81	V	-
195/50R16	88	VXL	-
205/50R16	87	W	-
225/50R16	96	WXL	-
195/55R16	87	W	-
205/55R16	91	W	-
205/55R16	94	WXL	-
215/55R16	97	WXL	-
225/55R16	99	WXL	-
195/60R16	89	H	-
195/40ZR17	81	WXL	-
205/40R17	84	WXL	-
215/40R17	87	WXL	-
245/40ZR17	95	WXL	-
195/45ZR17	85	WXL	-
205/45R17	88	WXL	-
215/45R17	91	WXL	-
225/45R17	94	WXL	-
235/45R17	97	WXL	-
245/45ZR17	99	WXL	-
205/50R17	93	WXL	-
215/50R17	95	WXL	-
225/50R17	98	WXL	-
235/50R17	96	W	-
215/55R17	98	WXL	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
225/55R17	101	WXL	-
235/55R17	103	WXL	-
215/35R18	84	WXL	-
255/35ZR18	94	WXL	-
265/35ZR18	93	W	-
215/40ZR18	85	W	-
225/40R18	92	WXL	-
235/40R18	95	WXL	-
245/40ZR18	97	WXL	-
255/40ZR18	99	WXL	-
215/45ZR18	89	W	-
225/45ZR18	95	WXL	-
235/45ZR18	98	WXL	-
245/45ZR18	100	WXL	-
215/50R18	92	V	-
225/50R18	95	V	-
235/50ZR18	101	WXL	-
245/50ZR18	100	W	-
235/55R18	104	VXL	-
265/30ZR19	93	WXL	-
225/35ZR19	84	W	-
235/35ZR19	91	WXL	-
245/35ZR19	93	WXL	-
235/40ZR19	92	W	-
245/40ZR19	98	WXL	-
275/40ZR19	101	W	-
245/45ZR19	98	W	-
275/30ZR20	93	W	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
225/35ZR20	90	WXL	-
245/35ZR20	95	WXL	-
275/35ZR20	98	W	-
315/35ZR20	110	WXL	-
245/40ZR20	95	W	-
255/40ZR20	101	WXL	-
275/40ZR20	106	WXL	-
245/45ZR20	99	W	-
275/45ZR20	110	WXL	-
275/55R20	117	VXL	-
245/30ZR22	92	WXL	-
245/35ZR22	97	WXL	-
305/40ZR22	114	WXL	-
205/45RF17	84	W	-
225/45RF17	91	W	-
205/50RF17	93	WXL	-
225/50ZRF17	94	W	-
225/55RF17	97	W	-
225/40RF18	88	W	-
245/40ZRF18	93	W	-
225/45ZRF18	91	W	-
245/45ZRF18	96	W	-
245/50ZRF18	100	WXL	-
245/50ZRF18	100	W	-
245/50ZRF18	100	W	-
235/55RF18	100	V	-
235/55RF18	104	VXL	-
275/40ZRF19	101	W	-
245/45ZRF19	98	W	-
245/45ZRF19	98	W	-



- Four grooves with open shoulder provides perfect water evacuation.
- Center rib design delivers better straight handling.
- Improved shoulder sipes provide better handling during cornering and low noise emission.

VANTI TOURING Z3

SIZE	LOAD INDEX	SPEED RANGE	PLY
165/65R13	77	T	-
165/60R14	75	T	-
185/60R14	82	H	-
195/60R14	86	H	-
205/60R14	88	V	-
185/70R14	88	H	-
195/70R14	91	H	-
205/70R14	98	VXL	-
195/50R15	82	V	-
185/55R15	82	V	-
195/55R15	85	V	-
185/60R15	84	H	-
195/60R15	88	V	-
205/60R15	91	V	-
185/65R15	88	H	-
185/65R15	92	TXL	-
195/65R15	91	V	-
195/65R15	95	HXL	-
205/65R15	94	H	-
205/65R15	94	V	-
P215/75R15	100	H	-
P225/75R15	104	V	-
205/55R16	91	V	-
205/60R16	92	V	-
205/60R16	96	VXL	-
215/60R16	95	V	-
215/60R16	99	VXL	-
225/60R16	98	V	-
215/65R16	98	V	-



- Four grooves with open shoulder provides perfect water evacuation.
- Center rib design delivers better straight handling.
- Improved shoulder sipes provide better handling during cornering and low noise emission.

VANTI TOURING S1

SIZE	LOAD INDEX	SPEED RANGE	PLY
185/60R14	82	H	-
195/60R14	86	H	-
205/60R14	88	V	-
185/65R14	86	H	-
185/70R14	88	H	-
195/70R14	91	H	-
205/70R14	98	HXL	-
195/50R15	82	V	-
185/55R15	82	V	-
195/55R15	85	V	-
185/60R15	84	H	-
195/60R15	88	V	-
205/60R15	91	V	-
175/65R15	84	H	-
185/65R15	88	H	-
195/65R15	91	V	-
205/65R15	94	V	-
215/75R15	100	H	-
225/75R15	102	H	-
205/55R16	91	V	-
205/60R16	92	V	-
215/60R16	95	V	-
225/60R16	98	V	-
205/65R16	95	V	-
215/65R16	98	V	-



VANTI 306

SIZE	LOAD INDEX	SPEED RANGE	SIDE WALL
185/75R14	89	T	WSW
205/75R14	95	T	WSW
205/75R15	97	T	WSW
215/75R15	100	T	WSW
225/75R15	102	H	WSW

- Combined design of multi-pitch tread pattern effectively reduces resonance noise of tread pattern surface.
- Reasonable groove and steel sheet distribution achieves more even pressure, reduces generation of eccentric wear, and improves wearability.
- Upgraded tread formula furnishes extraordinary wet braking and handling performance.
- Straight-groove design of tire shoulder effectively reduces splashing height and brings superior drainage performance.



COMMERCIAL



- Special compound design ensures a long mileage.
- The combination of blocks provides a superior driving performance and a strong grip.
- Three main grooves contribute to better water drainage and wet traction.

COMMERCIAL

SIZE	LOAD INDEX	SPEED RANGE	PLY
175/70R14LT	95/93	R	6PR
185R14C	102/100	Q	8PR
195R14C	106/104	Q	8PR
195R15C	106/104	Q	8PR
195/70R15C	104/102	R	8PR
205/70R15C	106/104	R	8PR
225/70R15C	112/110	R	8PR
215/75R15LT	100/97	N	6PR
195/65R16C	104/102	R	8PR
205/65R16C	107/105	R	8PR
215/65R16C	109/107	R	8PR
225/65R16C	112/110	R	8PR
235/65R16C	115/113	R	8PR
215/70R16LT	104/102	N	8PR
185/75R16C	104/102	R	8PR
195/75R16C	107/105	R	8PR
215/75R16C	116/114	R	10PR



VANTI 516

SIZE	LOAD INDEX	SPEED RANGE	PLY	SIDE WALL
195R14C	106/104	Q	8PR	BSW
195R15C	106/104	Q	8PR	BSW
195R14C	106/104	Q	8PR	WSW
195R15C	106/104	Q	8PR	WSW



- High-strength belt and cord provide strong support.
- High-saturation deepened pattern enhances pattern block rigidity and increases mileage.
- Three bending grooves in the center allow for faster water drainage, preventing aquaplaning and slippage.
- Unique light-truck tread formula furnishes excellent durable and wear-resistant quality.



COMMERCIAL 512

SIZE	LOAD INDEX	SPEED RANGE	PLY	SIDE WALL
5.00R12LT	88/86	P	10PR	BSW
5.00R12LT	88/86	P	10PR	WSW



- Optimized structure design technology reduces calorific value of tire casing and improve the durability.
- Reinforced tread and tire casing structure improves tire elasticity and guarantees stronger resistance to road impact.
- Coordination of two zigzag main grooves plus transverse grooves balances driving stability and traction performance.
- Design of three groups of longitudinal steel sheet grooves with continuous bending improves grip performance on dry and wet roads.



VANTI AS



- Optimized pitch design effectively reduces tire noise.
- Anti-slip sipe improves driving stability and braking performance on wet road.
- Streamline transversal grooves ensure safe handling and high speed stability.

VANTI AS

SIZE	LOAD INDEX	SPEED RANGE	PLY
155R12C	83/81	Q	6PR
155R12C	88/86	Q	8PR
145/70R12	69	T	-
175/70R12	80	T	-
175/60R13	77	H	-
155/65R13	73	T	-
165/65R13	77	T	-
145/70R13	74	N	-
155/70R13	75	T	-
165/70R13	79	T	-
175/70R13	82	H	-
175/70R13	82	T	-
185/70R13	86	T	-
135/80R13	70	T	-
155/80R13	79	T	-
165/80R13	83	T	-
175/65R14	82	H	-
175/65R14	86	TXL	-
165/70R14	81	T	-
175/70R14	84	H	-
175/70R14	88	TXL	-
185/70R14	88	H	-



VANTI 106



- 3 wide-and-deep ditches help improve the handling performance for driving on wet land in rainy days.
- Enlarged pattern blocks of tread are interlaced with the transverse fine grooves, enhancing high-speed traction performance.
- Optimized contour design makes the vehicle more stable and provides comfortable driving experience.
- Highly saturated pattern and excellent structural design improve operation response during driving and shorten braking distance.

VANTI 106

SIZE	LOAD INDEX	SPEED RANGE	SIDE WALL
165/65R13	77	T	WSW
185/60R13	80	V	WSW
175/70R13	82	T	WSW
185/65R14	86	H	WSW
185/70R14	88	H	WSW



VANTI TAXI



- Improved formula enhances unit wear performance of tread rubber, making it more suitable for the needs of taxi owners and offering longer mileage and cost effectiveness.
- Design of special tire profile and internal structure enhances the tire's capacity of absorbing impact and vibration during driving, substantially improving tire comfort; pitches of varied sizes of patterns offset the noise, making the driving more quiet.
- Design of shoulder with large pattern blocks connected by strong ribs ensures shoulder rigidity and improves steering performance of vehicle, which is suitable for taxi's characteristics of frequent lane change and turning.
- Extended area of pattern block betters wear resistance of tire; large tread block lengthens overall service life, strengthens grip and improves handling stability.

VANTI TAXI

SIZE	LOAD INDEX	SPEED RANGE	PLY
165/70R13	79	T	-
175/70R13	82	H	-
185/70R13	86	T	-
185/60R14	82	H	-
195/60R14	86	H	-
175/65R14	82	H	-
185/65R14	86	H	-
175/70R14	84	T	-
185/70R14	88	H	-
185/60R15	84	H	-
195/60R15	88	H	-
185/65R15	88	H	-
195/65R15	91	H	-
205/65R15	94	V	-
205/55R16	94	VXL	-



KARRIER MAX



- Suitable for various light-load goods vehicles.
- Excellent traction, braking and steering performance combined with good water dispersion and self-cleaning ability.

KARRIER MAX

SIZE	LOAD INDEX	SPEED RANGE	PLY
6.00R13LT(C)	93/89	P	8PR
6.00R14LT(C)	95/90	P	8PR
6.00R15LT(C)	97/92	P	8PR
6.00R16LT	107/102	M	10PR
6.50R16LT	107/102	M	10PR
7.00R16LT	113/111	M	10PR
7.00R16LT	117/116	N	12PR
7.50R16LT	123/121	M	14PR



MILEMAX



- Optimized structure design technology reduces calorific value of tire casing and improve the durability.
- Reinforced tread and tire casing structure improves tire elasticity and guarantees stronger resistance to road impact.
- Coordination of two zigzag main grooves plus transverse grooves balances driving stability and traction performance.
- Design of three groups of longitudinal steel sheet grooves with continuous bending improves grip performance on dry and wet roads.

MILEMAX

SIZE	LOAD INDEX	SPEED RANGE	PLY
165/70R13LT	88/86	T	6PR
155R13C	90/88	N	8PR
165R13C	94/93	N	8PR
165/70R14LT	89/87	R	6PR
175R13C	97/95	Q	8PR



TERRENA M/T



- Especially designed for unpaved tough roads.
- Various shoulder blocks promote driving and handling performance on tough roads.
- Perfect grip on tough surfaces such as mud and sand.

TERRENA M/T

SIZE	LOAD INDEX	SPEED RANGE	PLY
31X10.50R15LT	109	Q	6PR
33X12.50R15LT	108	Q	6PR
LT235/75R16	117/114	Q	10PR
LT245/75R16	120/116	N	10PR
LT265/75R16	123/120	N	10PR
LT285/75R16	122/119	Q	8PR
LT235/85R16	120/116	N	10PR
35X12.50R17LT	119	Q	8PR
LT265/70R17	121/118	Q	10PR
LT285/70R17	121/118	Q	8PR
35X12.50R18LT	123	Q	10PR
LT275/70R18	125/122	Q	10PR
35X12.50R20LT	121	Q	10PR

**VANTI WINTER**

SIZE	LOAD INDEX	SPEED RANGE	PLY
165/70R13	79	T	-
175/70R13	82	T	-
185/60R14	82	H	-
175/65R14	86	TXL	-
185/65R14	90	HXL	-
185/70R14	88	T	-
195/55R15	85	T	-
195/60R15	88	H	-
185/65R15	88	H	-
195/65R15	91	H	-
205/65R15	94	T	-
205/70R15	96	T	-
215/70R15	98	T	-
215/75R15	100	T	-
205/55R16	94	HXL	-
215/55R16	97	VXL	-
215/60R16	99	HXL	-
225/60R16	102	HXL	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
215/65R16	98	H	-
255/65R16	109	H	-
215/70R16	100	H	-
235/70R16	109	HXL	-
225/45R17	94	VXL	-
225/50R17	98	VXL	-
215/55R17	98	VXL	-
225/55R17	101	VXL	-
235/55R17	103	VXL	-
215/60R17	96	H	-
225/60R17	99	H	-
225/65R17	102	H	-
235/65R17	108	VXL	-
225/40R18	92	VXL	-
235/40R18	95	VXL	-
225/45R18	95	VXL	-
235/45R18	98	VXL	-
255/55R18	109	HXL	-
235/60R18	107	VXL	-



- Serrated design in the outside main groove assures high grip and braking force on ICE&SNOW covered surfaces.
- Deep and densely distributed grooves and steel sheet helps soften the tread, contributes to shorten braking distance on ice covered surface.

SNOW CUTTER

SIZE	LOAD INDEX	SPEED RANGE	PLY
175/70R13	82	T	-
175/65R14	82	T	-
185/65R14	90	TXL	-
195/60R15	88	T	-
185/65R15	88	T	-
195/65R15	91	T	-
205/65R15	94	T	-
205/70R15	96	T	-
215/70R15	98	T	-
205/55R16	91	T	-
205/55R16	94	TXL	-
205/60R16	92	T	-
215/60R16	95	T	-
225/60R16	102	TXL	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
215/65R16	98	T	-
215/70R16	100	T	-
235/70R16	109	TXL	-
LT245/75R16	120/116	-	10PR
245/45R17	95	T	-
225/65R17	102	T	-
235/65R17	104	T	-
265/70R17	115	T	-
LT265/70R17	121/118	-	10PR



WINTER 621

SIZE	LOAD INDEX	SPEED RANGE	PLY
155/65R13	73	T	-
185/60R14	82	T	-
175/70R14	84	T	-
185/70R14	88	T	-
195/55R15	85	T	-
185/60R15	84	T	-
195/60R15	88	T	-
185/65R15	88	T	-
195/65R15	91	T	-
195/55R16	87	T	-
205/55R16	90	T	-
225/55R16	95	T	-
195/60R16	89	T	-
205/60R16	92	T	-
215/60R16	95	T	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
245/45R17	95	T	-
205/50R17	89	T	-
215/50R17	91	T	-
225/50R17	94	T	-
205/55R17	91	H	-
215/55R17	94	T	-
225/55R17	97	T	-
245/45R18	96	T	-
225/50R18	95	H	-
235/40R19	96	TXL	-
235/45R19	95	T	-
245/45R19	102	HXL	-
255/45R19	100	H	-
255/40R20	101	TXL	-



- Special composite tread formula enables upper rubber to maintain softness and elasticity at low temperature and lower rubber to maintain overall rigidity of tire.
- Various kinds of crossed patterns effectively contain ice and snow, forming a high-strength snow column when driving on snowy roads and providing effective driving and braking capabilities for tire.
- More smaller pattern blocks and pattern grooves with optimal density evenly distribute tread pressure, significantly improving road adhesion of tire.
- Design of intrusive transverse pattern groove extending from the tire shoulder to the center strengthens anti-skid performance and traction of tire on curves.

WINTER 626

SIZE	LOAD INDEX	SPEED RANGE	PLY
235/75R15	105	T	-
215/65R16	98	T	-
235/70R16	109	TXL	-
265/70R16	112	T	-
215/60R17	96	T	-
225/60R17	99	T	-
225/65R17	102	T	-
245/65R17	107	T	-
265/65R17	112	T	-
235/50R18	97	T	-
215/55R18	95	T	-
225/55R18	98	T	-
235/55R18	100	T	-
225/60R18	100	T	-
235/60R18	103	T	-
245/60R18	105	T	-
265/60R18	110	H	-
235/65R18	106	T	-
265/65R18	114	T	-
235/50R19	99	H	-
255/50R19	107	HXL	-

SIZE	LOAD INDEX	SPEED RANGE	PLY
225/55R19	99	H	-
235/55R19	101	T	-
245/55R19	103	T	-
255/55R19	111	HXL	-
265/55R19	113	TXL	-
235/60R19	107	TXL	-
255/60R19	109	T	-
275/40R20	106	HXL	-
235/45R20	100	HXL	-
245/45R20	103	TXL	-
255/45R20	105	TXL	-
275/45R20	110	HXL	-
235/50R20	104	TXL	-
245/50R20	102	T	-
255/50R20	109	TXL	-
235/55R20	102	T	-
255/55R20	110	TXL	-
265/45R21	108	HXL	-



WINTER 628

- Specially designed tread load formula. The upper layer of rubber can still remain soft and elastic at low temperatures, and the lower layer of rubber can maintain the overall rigidity of the tire.
- The dense steel sheet design enhances the rigidity of the pattern while ensuring the softness and elasticity of the original tire formula. It can break the water film with more and finer slit patterns and inhibit tire slippage.
- A stronger carcass structure design gives the tire a greater load-carrying capacity and ensures driving safety of the tire under loaded conditions.
- Deeper tread depth and larger tread surface area make it less likely for the tire to cut off snow pillars and ice pillars when driving, increasing the snow and ice removal capacity and providing stronger drivability and braking for the tire. At the same time, the angular design of the shoulder area can effectively prevent tire sideslip when the vehicle turns.

WINTER 628

SIZE	LOAD INDEX	SPEED RANGE	PLY
175R14LT	94/92	S	6PR
185R14C	102/100	Q	8PR
185R15C	103/102	Q	8PR
195/70R15C	99/96	R	8PR
6.50R16C	107/102	M	10PR
7.00R16C	111/107	M	10PR



WINTER RX858

- Combination of left-right symmetrical "herringbone" pattern design, widened transverse grooves, fine steel sheets, and patterns studded with steel nails improves tire grip when driving on ice-and-snow-covered roads.
- Optimized fine seam depth of pattern plus strengthened pattern realize balanced functions on ice, snow, dry and wet roads.
- Optimized sea-land ratio improves the guiding stability of driving on roads and increases contact area between tread and road surface, ensuring excellent ice and snow braking performance of tire.
- Low-temperature-resistant formula enables tire to maintain relatively low rubber hardness, featuring relatively strong low-temperature performance.

WINTER RX858

SIZE	LOAD INDEX	SPEED RANGE	PLY
215/70R15	98	S	-
LT235/75R15	110/107	Q	8PR
LT225/75R16	115/112	Q	10PR
LT265/75R16	123/120	Q	10PR
LT285/75R16	126/123	Q	10PR
LT235/85R16	120/116	Q	10PR
225/60R17	99	T	-
LT245/70R17	119/116	Q	10PR
LT275/65R18	123/120	Q	10PR
LT275/70R18	125/122	Q	10PR